



HD / 1,280 x 720 H.264 Weather Proof Camera featuring 45x HD extra optical zoom and Super Dynamic

Key Features



- 720p HD images up to 30 fps
- Super high resolution at HD / 1,280 x 720
- Multiple H.264 (High profile) streams and JPEG streams ensure simultaneous real time monitoring and high resolution recording.
- Full frame (Up to 30 fps) transmission at 1,280 x 960 image size
- **30x optical zoom, 45x HD extra optical zoom at 1,280 x 720**
90x extra optical zoom at 640x360 resolution with 12x digital zoom enabling 1080x zoom.
- **Super Dynamic** and ABS (Adaptive Black Stretch) technologies deliver 128x wider dynamic range compared to conventional cameras.
- **Face Super Dynamic** technology ensures clear face image.
- High sensitivity with Day/Night (ICR*) function:
0.1 lx (Color), 0.013 lx (B/W) at F1.6
*ICR: IR Cut filter Removal
- **VIQS** (Variable Image Quality on Specified area) technology allows the designated **2 areas** to retain higher image quality while the excluded area will have a decreased image quality, which enables to use lower image file size and bit rate.
VIQS can be set on preset position (1 to 8) and except preset.
- **Smart coding Technology** : Group of Pictures (GOP) control function removes unnecessary information from the frame for realizing efficient encoding.
- Electronic sensitivity enhancement: Auto (Up to 16x) / OFF
- Selectable light control modes:
Outdoor scene / Indoor scene (50 Hz) / Indoor scene (60 Hz) / Fix shutter
Indoor scene (50 Hz / 60 Hz): Flicker caused by fluorescent lightning will be automatically compensated.
- **360 degrees endless Panning**
- Advanced auto tracking: The camera automatically pans and tilts to follow a moving subject and keep it in the center of the image.
- PTZ control can be taken very smoothly on the user friendly GUI with 16 speeds pan/tilt and "Drag and Zoom" operation enabling finer control. 256 speeds available for system with WV-CU950 system controller.
- Up to 256 preset positions
- 360 map shot: 8 thumbnail images at 45 deg. intervals make it simple to direct the camera easily by clicking on a thumbnail.
- Industrial grade Pan / Tilt / Zoom mechanism for high reliability
- VMD (Video Motion Detection) with 4 programmable detection areas, 15 steps sensitivity level and 10 steps detection size
- Privacy Zone can mask up to 32 private areas, such as house windows and entrances/exits.
- Camera title display: Up to 20 alphanumeric characters on the browser
- Alarm sources including 3 terminal input, VMD and Panasonic alarm command can trigger actions such as SDXC/SDHC/SD memory cording, FTP image transfer, E-mail notification, Indication on browser, Alarm terminal output, and Panasonic alarm protocol output.

- Full duplex bi-directional audio allows interactive communication between camera site and monitoring site.
- JPEG Image compression ratio can be changed by alarm so that higher quality image can be provided.
- Prioritized stream control: One of the video streams can be prioritized when multiple recorders or client PCs are accessing the camera so that the recorder or the client PC can maintain the frame rate.
- SDXC/SDHC/SD Memory card slot for manual recording (H.264 / JPEG), alarm recording (H.264 / JPEG) and backup upon network failure (H.264 / JPEG)
- H.264 max. bit rate / client and Total bit rate control allows flexible network traffic management. Frame rate priority mode controls bit rate and compression ratio to provide the specified frame rate.
- Internet mode: H.264 images can be transmitted over HTTP protocol.
- Multi-language: English / Italian / French / German / Spanish / Portuguese / Russian / Chinese / Japanese
- Supports SSL, DDNS (viewnetcam, RFC2136)
- Still images (JPEG) can be viewed on mobile phones via Internet.
- IP66 rated water and dust resistant. Compatible with IEC60529 measurement standard compliant.
- Dehumidification device for use in various weather conditions
- **Rain wash coating dome cover**
- Ambient Operating Temperature : -50 °C to +55 °C (-58 °F to 131 °F)
- **Fog compensation function** equipped as standard.
- AEM (Auto Eyelid Mechanism) offers images that are more natural and easy to watch reducing doubled images when direction of the lens moved above the horizontal.

Standard Accessories

<ul style="list-style-type: none"> • Installation Guide.....1 pc. • CD-ROM*1.....1 pc. • Code Label*2.....1 pc. 	<p>The followings are for installation.</p> <ul style="list-style-type: none"> • Protection Cover 1 pc. • Cable coupler (used with the network cable) ..1 pc. • 8P Alarm Cable..... 1 pc. • 24 V AC power supply connector kit 1 pc. • Front/Rear Sun Shield..... 1 set • Front/Rear Sun Shield Fixing Screws 2 pcs. (incl. 1 spare)
<p>*1 The CD-ROM contains the operating instructions (PDFs) and different kinds of tool software programs.</p> <p>*2 This label may be required for network management. The network administrator shall retain the code label.</p>	

Optional Accessories

<p>Ceiling Mount Bracket WV-Q121B</p> 	<p>Wall Mount Bracket WV-Q122A</p> 
--	---

Specifications

Camera	Image Sensor	Approx. 1/3 type MOS image sensor	
	Scanning Mode	Progressive scan	
	Scanning Area	5.35 mm (H) x 3.34 mm (V) (7/32 inches(H) x 1/8 inches(V))	
	Minimum Illumination	Color: 0.1 lx, BW: 0.013 lx (F1.6, Auto slow shutter: Off (1/30s), Gain: On(High)) Color: 0.007 lx, BW: 0.001 lx (F1.6, Auto slow shutter: Max. 16/30s, Gain: On(High)) ^{*1}	
	White Balance	AWC (2,000 - 10,000 K), ATW1 (2,700 - 6,000 K), ATW2 (2,000 - 6,000 K)	
	Light Control Mode	Outdoor scene: Automatic integration of ALC and ELC Indoor scene [50 Hz]: Automatic integration of ALC and ELC (up to 1/100 s) Indoor scene [60 Hz]: Automatic integration of ALC and ELC (up to 1/120 s) Fix shutter	
	Shutter Speed	Fix shutter: 1/30, 3/100, 3/120, 2/100, 2/120, 1/100, 1/120, 1/250, 1/500, 1/1,000, 1/2,000, 1/4,000, 1/10,000	
	Super Dynamic	On / Off	
	Face Super Dynamic	On / Off	
	Dynamic Range	105 dB typical (Super Dynamic: On, Light Control mode: Indoor) ^{*Theoretical value. Conventional measuring method: 52 dB}	
	Adaptive Black Stretch	On / Off	
	Fog compensation	On / Off (Super Dynamic and Adaptive black stretch: Off)	
	Gain (AGC)	On (High) / On (Mid) / On (Low) / Off	
	Auto slow shutter	Off (1/30 s), max. 2/30 s, max. 4/30 s, max. 6/30 s, max. 10/30 s, max. 16/30 s	
	Day/Night (ICR)	Mode: AUTO1 / AUTO2 / AUTO3 / On / Off Level : High / Low, with external control	
	Digital Noise Reduction	High / Low	
	Video Motion Detection	4 areas, Sensitivity: 15 steps, Detection size: 10 steps	
	Privacy Zone	Gray / Mosaic / Off (up to 32 zones available)	
	Image Stabilizer	On / Off	
	VIOS	On / Off Up to 2 zones at preset position 1-8 and except preset	
	Double Image Reduction	On / Off	
	Camera Title (OSD)	On / Off Up to 20 characters (alphanumeric characters, marks)	
	Focus distance	Limited (around 1.5m(4.9 ft)) / Unlimited	
	Focal Length	4.3 mm - 129.0 mm (3/16 inches - 5-3/32 inches)	
	Zoom Ratio	30x / 45x with HD extra optical zoom (at 1280 x 720)	
	Digital (Electrical) Zoom	12x (Max. 1080x combined with extra optical zoom at 640 x 360)	
	Angular Field of View	[16 : 9 mode] Horizontal: 2.6° (TELE) - 63° (WIDE) Vertical : 1.5° (TELE) - 37° (WIDE) [4 : 3 mode] Horizontal: 1.9° (TELE) - 46° (WIDE) Vertical : 1.5° (TELE) - 37° (WIDE)	
Maximum Aperture Ratio	1 : 1.6 (WIDE) - 4.7 (TELE)		
Focusing Range	2.0 m - ∞		
Aperture Range	F1.6 - Close		
Pan and Tilt	Panning Range	360° endless	
	Panning Speed	Manual: approx. 0.065°/s to 120°/s, Up to 256 steps (depending on the controller) Preset : up to approx. 300°/s	
	Tilting Range	-15° to 195° (upward-level-downward) Auto Eyelid Mechanism (Double image reduction) Selectable tilting angle: 10 ° 5 ' 3 " 0 ° 2 ' -3 ° 2 ' -5 ° 2 ' -10 ° 2 ' -15 ° 2 '	
	Tilting Speed	Manual: approx. 0.065°/s to 120°/s, Preset: up to approx. 300°/s	
	Proportional Pan/Tilt Control	Yes	
	Number of Preset Positions	256	
	Auto Mode	Auto track / Auto pan / Preset sequence / 360 map-shot / Patrol	
	Image Hold	On / Off	
	Camera position display	Off / Pan-Tilt degree - Zoom ratio display / Direction display	
	Self Return	10 s / 20 s / 30 s / 1 min / 2 min / 3 min / 5 min / 10 min / 20 min / 30 min / 60 min	
	Map Shot	360° map shot / Preset map shot	
	Browser GUI	Camera Control	Pan/Tilt (256 steps), Zoom, Focus, Click centering, Drag zoom, Iris, Preset position call and program, Auto mode
		Display Mode	Spot, Quad: Image from 16 cameras can be displayed in 4 different Quad screens or 16 split screen (JPEG only), 20 characters camera title available.
Camera Title		Up to 20 alphanumeric characters (alphanumeric characters, marks)	
Clock Display		Time: 12H/24H, Date: 5 formats on the browser, Summer time (Manual)	
Alarm Control		Reset	
One Shot Capture		A still picture will be displayed on a newly opened window.	
Audio		Mic (Line) Input: On / Off Volume adjustment : Low / Middle / High Audio Output : On / Off Volume adjustment : Low / Middle / High	
SD Memory Data Download		Still or motion Images recorded in the SDXC/SDHC/SD memory card can be downloaded.	
GUI/Setup Menu Language		English / Italian / French / German / Spanish / Portuguese / Russian / Chinese / Japanese	
System Log		Up to 100 (Internal) Up to 4,000 (SDXC/SDHC/SD memory when the recording format is set to JPEG.) error logs	
Supported OS ^{*3}		Microsoft® Windows® 10 Microsoft® Windows® 8.1 Microsoft® Windows® 8 Microsoft® Windows® 7 Microsoft® Windows Vista®	
Supported Browser		Windows® Internet Explorer® 11 (32 bit) Windows® Internet Explorer® 10 (32 bit) Windows® Internet Explorer® 9 (32 bit) Windows® Internet Explorer® 8 (32 bit) Windows® Internet Explorer® 7 (32 bit)	
Network		Network IF	10Base-T / 100Base-TX, RJ45 connector
	Image Resolution	• Image Capture Mode [16 : 9] (30 fps) 1,280 x 720 / 640 x 360 / 320 x 180	
	H.264 JPEG (MJPEG)	• Image Capture Mode [4 : 3] (30 fps) 1,280 x 960 / 800 x 600 / 640 x 480 / 320 x 240	
	H.264 ^{*4}	Transmission Mode	Constant bit rate / Variable bit rate / Frame rate priority / Best effort / Advanced VBR
		Frame Rate	1 / 3 / 5 / 7.5 / 10 / 12 / 15 / 20 / 30 fps
		Bit Rate/Cliet	64 / 128 / 256 / 384 / 512 / 768 / 1,024 / 1,536 / 2,048 / 3,072 / 4,096 / 6,144 / 8,192 / 10,240 / 12,288 / 14,336 kbps
		Image Quality	Low / Normal / Fine
	JPEG	Refresh Interval	0.2 / 0.25 / 0.33 / 0.5 / 1 / 2 / 3 / 4 / 5
		Transmission Type	Unicast / Multicast
	Audio Compression	Image Quality	0 SUPER FINE/ 1 FINE/ 2/ 3/ 4/ 5 NORMAL/ 6/ 7/ 8/ 9 LOW (10 steps: 0-9)
		Refresh Interval	0.1 fps to 30 fps
	Audio Mode	Transmission Type	Pull / Push
	Authentication for Audio	Audio Compression	G.726 (ADPCM) 32 kbps / 16 kbps, G.711 64 kbps, AAC ^{*5}
Total Bit Rate	Audio Mode	Off / Mic (Line) input / Audio output / Interactive (Half duplex) / Interactive (Full duplex)	
Supported Protocol	Authentication for Audio	Level 1 only / Level 2 higher / All users	
	Total Bit Rate	64 / 128 / 256 / 384 / 512 / 768 / 1,024 / 2,048 / 4,096 / 8,192 kbps / Unlimited	
	Supported Protocol	IPv6: TCP/IP, UDP/IP, HTTP, HTTPS, RTSP, RTP, RTP/RTCP, FTP, SMTP, DNS, NTP, SNMP, DHCPv6, ICMP, ARP IPv4: TCP/IP, UDP/IP, HTTP, HTTPS, RTSP, RTP, RTP/RTCP, FTP, SMTP, DHCP, DNS, DDNS, NTP, SNMP, UPnP, IGMP, ICMP, ARP	

Network	FTP Client	Alarm image transmission, FTP periodic transmission (When the FTP transmission is failed, backup on an optional SDXC/SDHC/SD memory card is available.)	
	Maximum concurrent access number	Up to 14 users (Depends on recording network conditions)	
	SDXC/SDHC/SD Memory Card (Option)	H.264 recording (Audio recording is enable): Manual REC / Alarm REC (Pre/Post) / Schedule REC / Backup upon network failure JPEG recording: Manual REC / Alarm REC (Pre/Post) / Backup upon network failure Compatible SD (SDHC/SDXC) card: Panasonic 2 GB, 4 GB*, 8 GB*, 16 GB*, 32 GB*, 64 GB**, 128 GB** model *SDHC card, ** SDXC card (except miniSD card and microSD card)	
	Cellular Phone Compatibility	JPEG image, panning / tilting / zoom / focus control, AUX control (by access level)	
	Mobile Terminal Compatibility	iPad, iPhone, iPod touch (iOS 4.2.1 or later) Android™ mobile terminals	
	Alarm	Alarm Source	3 terminals input, VMD, Command alarm, Audio detection
		Alarm Actions	SDXC/SDHC/SD memory recording, E-mail notification, Indication on browser, FTP image transfer, Panasonic protocol output
		Alarm Log	With SDXC / SDHC / SD memory card: 5,000 logs, without SDXC / SDHC / SD memory card: 1,000 logs
		Schedule	Alarm / VMD / Access permission / H.264 recording / Audio detection
	Input/ Output	Monitor Output (for adjustment)	VBS : 1.0V(p-p) / 75Ω, NTSC / PAL composite, BNC Jack
Microphone/Line Input		MIC IN and Line IN are selectable. ø3.5 mm monaural mini jack (Applicable microphone: Plug-in power type) Supply voltage: 2.5 V ±0.5 V Input impedance: approx. 2 kΩ	
Audio Output		ø3.5 mm stereo mini jack (monaural output) Line level	
External I/O Terminals		ALARM IN 1 (DAY/NIGHT IN), ALARM IN 2 (ALARM OUT), ALARM IN 3 (AUX OUT)	
General	Safety/EMC Standard	<Safety> UL (UL60950-1), C-UL (CAN/CSA C22.2 No.60950-1), CE, IEC60950-1 <EMC> FCC Part15 Class A, ICES-003 Class A, EN55022 Class B, EN55024	
	Power Source and Power Consumption	AC24 V : 3.5 A, 55 W PoE+ DC54 V : 470 mA, 25 W (IEEE802.3at compliant) Tested POE Injector (60 W) DC54 V : 1.0 A, 50 W	
	Ambient Operating Temperature	AC24 V and Tested PoE Injector (60 W) : -50 °C to +55 °C (-58 °F to 131 °F) POE+ : -30°C to +55°C (-22 °F to 131 °F)	
	Ambient Operating Humidity	10 % to 90 % (no condensation)	
	Shock resistance	Compliant with IK10 (IEC62262)	
	Water and Dust Resistance	Main body : IP66 (IEC60529) compliant, Type 4 (UL50), NEMA 4	
	Dimensions	ø229 mm x 392 mm(H) (ø9-1/32 inches x 15-7/16 inches(H)) diameter of the dome 160 mm(6-5/16 inches)	
	Mass (approx.)	Approx. 5.0 kg (11.02 lbs)	
	Finish	Main body : Aluminum die cast, Natural silver Sunshields : ASA resin coating, Natural silver Dome section : Clear polycarbonate resin (Rain wash coating)	

*1 Converted value


*2 If "0 °", "-3 °", "-5 °", "-10 °", or "-15 °" is selected, the area hidden by the camera housing may increase when the tilt angle of the camera is almost level. When "-15 °" is selected for "Tilt Angle", the upper half of images will be hidden.

*3 For further information about PC system requirements and precautions for when using Microsoft® Windows® 10, Microsoft® Windows® 8.1, Microsoft® Windows® 8, Microsoft® Windows® 7, Microsoft® Windows Vista®, or Windows Internet Explorer, click "Manual" - "Open" from the supplied CD-ROM and refer to "Notes on Windows® / Internet Explorer® versions".


*4 Transmission for 2 streams can be individually set.

*5 When recording audio on an SD memory card, only AAC-LC (Advanced Audio Coding - Low Complexity) is used.

Part Names and Functions



Appearance



Trademarks and registered trademarks

- Microsoft, Windows, Windows Vista, Windows Media, Internet Explorer, and ActiveX are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- Pad, iPhone, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.
- Android is a trademark of Google Inc.
- "MEGA Super Dynamic", "i-PRO SmartHD" logos are trademarks or registered trademarks of Panasonic Corporation.
- ONVIF and the ONVIF logo are trademarks of ONVIF Inc.

Important


- Safety Precaution: Carefully read the Installation Guide and operating instructions before using this product.
- Panasonic cannot be responsible for the performance of the network and/or other manufacturers' products used on the network.

- Masses and dimensions are approximate.
- Specifications are subject to change without notice.

DISTRIBUTED BY:

Panasonic

<http://security.panasonic.com>

 <http://www.facebook.com/PanasonicNetworkCamera>

(2A-164AL)